																					TRUNION			CLEVIS					FOOT				
BORE	ROD	RD	RL	ØLD	MT	PG	TS	TD	R	PP	ET	EG	OL	NH	ES	FF	BB	BL	ØMH	FT	TUL	ØTUD	TUW	EM	CR	ØCD	CC	CT	LL	EL	FH	FC	FL
40	18	M16x1.5	20	36	5	3/8"BSP	12.5	13	1.0	90	45	55	143	18	70	118	40	94	14	18	20.0	20.0	30	20	16	16	25	13	15	30	13	40	95
50	22	M20x1,5	25	42	10	1/2"BSP	12.5	16	1.0	92	50	60	147	18	85	135	50	108	14	20	25.0	25.0	40	25	20	20	32	16	15	30	18	50	97
63	28	M24x1.5	32	50	10	1/2"BSP		20		92	62	60	147	24	100	160	65	130	18		31.5	31.5	50	40	31	31.5	40	20	15	30	20	60	97
70	32	M26x1.5	32	55	10	1/2"BSP	15.0	22	1.5	97	62	70	152	24	110	170	70	138	18	20	31.5	31.5	50	40	31	31.5	40	20	15	30	20	65	102
80	36	M30x1.5	36	65	10	3/4"BSP		25		108	66	70	175	24	122	185	80	150		25			58	40	31	31.5	40	20	17	34	22	70	116
90	40	M36x1.5	40	65	10	3/4"BSP	15.0	28	2.0	114	75	75	181	24	128	190	90	158	18	25	40.0	40.0	60	50	40	40	50	25	17	34	25	75	122
100	45	M40x1.5	45	70	10	3/4"BSP		31		114	80	75	186	28	145	220	100	180	22	30			60	50	40	40	50	25	17	34	25	85	122
110	50	M45x1.5	50	80	10	3/4"BSP	20.0	35	2.0	119	85	90	191	28	160	235	115	196	22	30	50.0	50.0	70	65	50	50	63	32	17	34	30	95	127
125	56	M50x1.5	56	85	10	3/4"BSP		38		121	96	90	199	32	175	255	125	210	26	32			70	65	50	50	63	32	18	36	30	100	131
140	63	M58x2.0	63	90	10	3/4"BSP	20.0	43	3.0	126	103	100	208	32	195	295	140	240	26	36	60.0	60.0	83	85	63	63	80	40	18	36	35	115	136
150	65	M62x2.0	67	105	10	3/4"BSP	25.0	46		133	117	110	217	40	212	305	150	254	33	37			85	85	63	63	80	40	24	48	35	120	132
160	70	M65x2.0	70	105	10	3/4"BSP	25.0	49	3.5	133	120	115	223	40	224	335	160	275	33	41	70.0	70.0	90	95	70	70	80	40	24	48	42	130	141
180	80	M75x2.0	80	115	10	3/4"BSP		55	4.0	146	135	115	241	40	250	365	180	300		45	80.0	80.0	100	100	80	80	100	50	24	48	47	140	148
200	90	M85x2.0	90	125	10	3/4"BSP	30.0	60	5.0	155	150	130	255	48	280	405	210	335	39	50	90.0	90.0	110	120	90	90	125	63	30	60	52	160	145

ORDERING DETAILS

T 1 6 0 - 1 0 0 - 0 4 5 - 3 0 0 - R F 1 - C B - V i - P T - S

- TIE-ROD
- PRESSURE
- BORE
- ROD
- STROKE
- MOUNTING
- CUSHION
- SEALS
- PORT
- S-SLOT / T-THREADED

CUSHIONING :-

NC : NON-CUSHIONED CH : AT HEAD END ONLY

CB : AT BOTH ENDS CC : AT CAP END ONLY

SEALS :- Ni : NITRILE Vi : VITON PU : POLY EURETHENE

PORT: PT - TOP PSR - R.H. PSL - L.H.

E-mail: vinayakhanolkar@vsnl.net

MOUNTING DIMN. DETAILS	SHEET NO. 7 OF 7
	DRAWN BY VBK
DRG. NO. VMPL\NAMBU\091102	CHK. BY VBK.

VEEKHOY METALIKA PVT. LTD.
S-218, MIDC BHOSARI, PUNE 411026.